

CLAIMS

I claim:

1. A hat mountable flag device for removably positioning on a hat, said device comprising:
 - a rod being elongated and having a first end and a second end;
 - a flag being mounted on said rod; and
 - a fastener being attached to said second end of said rod for removably attaching said rod to the hat.
2. The device of claim 1, wherein said rod has a break therein such that a first section and a second section of said rod is defined, a coupler being attached to said first and second sections for pivotally coupling said first and second sections together such that an angle between said first and second sections may selectively be chosen, said angle being generally from 45 degrees to 180 degrees.
3. The device of claim 2, wherein said flag comprises a rigid material and extends outwardly away from said rod.
4. The device of claim 1, wherein said flag comprises a rigid material and extends outwardly away from said rod.
5. The device of claim 2, wherein said fastener includes a U-shaped clip having a pair of legs and a central section extending between said legs, said rod being attached to one of said legs such that a longitudinal axis of said rod extends through each of said legs.
6. The device of claim 1, wherein said fastener includes a U-shaped clip having a pair of legs and a central section extending between

said legs, said rod being attached to one of said legs such that a longitudinal axis of said rod extends through each of said legs.

7. The device of claim 1, wherein said fastener includes a plate attached to said rod, said plate being positioned in a plane orientated generally perpendicular to a longitudinal axis of said rod, said plate having a peripheral edge having a slot extending therein.

8. The device of claim 2, wherein said fastener includes a plate attached to said rod, said plate being positioned in a plane orientated generally perpendicular to a longitudinal axis of said rod, said plate having a peripheral edge having a slot extending therein for removably receiving an upper button of the hat.

9. A hat mountable flag device for removably positioning on a hat, said device comprising:

- a rod being elongated and having a first end and a second end, said rod having a break therein such that a first section and a second section of said rod is defined, a coupler being attached to said first and second sections for pivotally coupling said first and second sections together such that an angle between said first and second sections may selectively be chosen, said angle being generally from 45 degrees to 180 degrees;

- a flag being mounted on said rod, said flag being positioned generally adjacent to said first end of said rod, said flag comprising a rigid material and extending outwardly away from said rod; and

- a fastener being attached to said second end of said rod for removably attaching said rod to the hat, said fastener including a U-shaped clip having a pair of legs and a central

section extending between said legs, said rod being attached to one of said legs such that a longitudinal axis of said rod extends through each of said legs.